

Cylinder Valve for RV and Small ASME System Vapor Withdrawal

Designed especially for vapor withdrawal service in small ASME containers with surface area up to 23.8 square feet. UL flow capacity is 645 CFM/air, per NFPA 58

Part Number	Container Connection	Service Connection	Fixed Liquid Level Vent Valve Style	Pressure Relief Valve Setting	For Use In Cylinders w/ Propane Capacity Up To:
3100CO	3/4" M. NGT	F. POL (CGA 510)	None	312 PSIG	ASME Tanks *

Cylinder Valve for Liquid Withdrawal

Equipped with excess flow valves and liquid withdrawal tubes, they are designed for liquid withdrawal of DOT cylinders up to 100 lbs propane capacity. They are most often used in heavy BTU loads found in industrial uses.


Part Number	Container Connection	Service Connection	Fixed Liquid Level Vent Valve Style	Dip Tube Length w/ Deflector	Liquid Withdrawal Tube Length	Pressure Relief Valve Setting	For Use In Cylinders w/ Propane Capacity Up To:
9107K8A	3/4" M. NGT	CGA 555	Knurled	11 9"	44"	375 PSIG	100 lbs



Cylinder Valve for Liquid Withdrawal

These cylinder valves may be used for liquid withdrawal from DOT cylinders with up to 100 lbs. propane capacity.


Part Number	Container Connection	Service Connection	Fixed Liquid Level Vent Valve Style	Dip Tube Length w/ Deflector	Pressure Relief Valve Setting	For Use In Cylinders w/ Propane Capacity Up To:
9107K2A	3/4" M. NGT	CGA 555	Knurled	None *	375 PSIG	100 lbs



Plumber Pot Cylinder Valves for Vapor Withdrawal

These valves are designed to allow the installation of a plumber's lead melting pot tripod to a DOT cylinder with propane capacities up to 42 lbs.

Part Number	Container Connection	Service Connection	Fixed Liquid Level Vent Valve Style	Dip Tube Length w/ Deflector	Pressure Relief Valve Setting	For Use In Cylinders w/ Propane Capacity Up To:
3547W	3/4" M. NGT	F. POL (CGA 510)	None	None	375 PSIG	42 lbs
8547VWN *			Knurled			



Dual Cylinder Valve for Simultaneous Liquid and Vapor Withdrawal

This dual cylinder valves was designed especially for industrial uses. It increases the cylinder's flexibility by permitting DOT cylinders up to 100 lbs. propane capacity to be used interchangeably or simultaneously for either liquid or vapor withdrawal.

Part Number	Container Connection	Service Connection		Fixed Liquid Level Vent Valve Style	Liquid Withdrawal Tube Length	Pressure Relief Valve Setting	For Use In Cylinders w/ Propane Capacity Up To:	Liquid Closing Flow (LPG-Gas) *
		Vapor	Liquid					
8866	3/4" M. NGT	F. POL (CGA 510)	CGA 555	None	44"	375 PSIG	100 lbs.	2.3 GPM

