


LPG & AMMONIA EQUIPMENT

F



External Pop Action Supplementary Pressure Relief Valves for small ASME Containers and DOT Cylinders.

Designed for use as a supplementary relief valve on a small ASME above ground and underground containers. They may also be used as a primary or secondary relief device on DOT cylinders, or as hydrostatic relief valves. All working components of these relief valves are outside the container connection, so the valves must be protected from physical damage.

Part Number	Container Type	Start To Discharge Setting PSIG	Container Conn. M. NPT	Flow Capacity SCFM/Air*		Suitable for Tanks with Surface Area Up To:***	Accessories		
				UL (At 120% of Set Pressure)	ECI Rated at 480 PSIG**		Protective Cap	Pipeway Adapters Part Number / Outlet Size	
3127G	ASME	250	1/2"	295	—	—	7545-40	—	
3129G			1/2"	485	—			3129-1C	1/2" F. NPT
3127K			1/4"	—	750			100 lbs/propane	—
3129K	DOT	375	1/2"	—	780	200 lbs/propane	—	3129-1C	1/2" F. NPT

External Hydrostatic Relief Valves


Designed for the protection of piping and shut-off valves where there is a possibility of trapping liquid LP-Gas. May be installed in pipelines and hoses located between shut-off valves or in the side boss of ECII shut-off valves.



Part Number	Start To Discharge Setting PSIG	Valve Body Material	Container Connection M. NPT	Accessories	
				Protective Cap	Pipeway Adapters Adapter or Threads
SS8001G	250	Stainless Steel	1/4"	—	—
SS8002G			1/2"		—
SS8021G			1/4"		1/4" NPSM Threads
SS8022G			1/2"		3/8" NPT Threads
3127G	275	Brass	1/4"	7545-40	—
3129G			1/2"		3129-10 *
3127H			1/4"		—
3129H			1/2"		3129-10 *
3127P	300	Brass	1/4"	—	—
3129P			1/2"		3129-10 *
3127J			1/4"		—
3129J			1/2"		3129-10 *
SS8001J	350	Stainless Steel	1/4"	—	—
SS8002J			1/2"		—
SS8021J			1/4"		1/4" NPSM Threads
SS8022J			1/2"		3/8" NPT Threads
3127K	375	Brass	1/4"	7545-40	—
3129K			1/2"	7545-40	3129-10 *
3125L			1/2"	Included	—
3127L			1/4"	7545-40	—
SS8001L	400	Stainless Steel	1/2"	—	—
SS8002L			1/4"		1/4" NPSM Threads
SS8021L			1/2"		3/8" NPT Threads
SS8022L			1/2"		—
3127U	450	Brass	1/4"	7545-40	—
3129U			1/2"	7545-40	3129-10 *
SS8001U			1/4"	—	—
SS8002U			1/2"	—	—
SS8021U	1/4"	—	1/4" NPSM Threads		
SS8022U	1/2"	—	3/8" NPT Threads		

Multiport Pressure Relief Valve Manifold Assemblies for Large Storage Containers

Designed especially for use as a primary relief device on large stationary pressurized storage containers with flanged openings. These manifolds incorporate an additional relief valves without evacuating the container. The handwheel on the manifold selectively closes off the entrance port for the container and its contents. All manifold flow ratings are based on flow through the relief valves after one has been removed for service or replacement.



Part Number	Consists of	For Use With	For Connection To:	Number Required
7560-55	1 - Exit Stud and Nut	All ECII Multiports	Modified 3" - 300# and 4" - ASA 300# Welding Neck Flange	6
7560-56			Manifold Cover Plate	

Part Number	Start To Discharge Setting PSIG	Application		Container Flange Connection	Quantity	Relief Valve Included		Flow Capacity SCFM / Air**	
		LP-Gas	NH3			Part Number	Inlet Connection M. NPT	UL (At 120% of Set Pressure)	ASME (At 120% of Set Pressure)
A8563G	250	Yes	Yes	3" - 300#	3	A3149MG	2 1/2"	16,500 (2)	6,292 (2)
AA8563G		No				A3136MJA	1 1/2"	11,400 (2)	—
A8564G		Yes				A3149MG	2 1/2"	27,750 (3)	24,439 (2)
A8573G		No		4" - 300#	3	A3136MJA	1 1/2"	16,500 (2)	6,292 (2)
A8574G		Yes				A3149MG	2 1/2"	27,500 (3)	24,439 (2)
A8563GC	275 (Cat.)	Yes	Yes	3" - 300#	3	A3149MGC	2 1/2"	—	16,292 (2)

