

## GREASE PRIMING PISTON PUMPS: LOW PRESSURE & HIGH PRESSURE:

Part No.	Ratio	Container Size	Air Motor Diameter in. (mm)	Max. Rec. Air Pressure psi (bar)	Max. Free-Flow Flow Rate lb./min. (kg/min.)	Approx. cpg (cpl)
<b>EAGLE</b>						
235-888	50:1	35 lb./12.5 kg	2.9 (73.7)	150 (10)	2.2 (1.0)	416 (110.2)
235-889	50:1	120 lb./55 kg	2.9 (73.7)	150 (10)	2.2 (1.0)	416 (110.2)
235-890	50:1	400 lb./180 kg	2.9 (73.7)	150 (10)	2.2 (1.0)	416 (110.2)
<b>FIRE-BALL</b>						
949-290*	5:1	Stubby	3 (76.2)	180 (12)	25 (11.3)	28 (7.4)
949-303*	5:1	120 lb./55 kg	3 (76.2)	180 (12)	25 (11.3)	28 (7.4)
949-041*	50:1	400 lb./180 kg	3 (76.2)	180 (12)	25 (11.3)	28 (7.4)
207-609	50:1	Pail Length	3 (76.2)	180 (12)	2.2 (1.0)	310 (82)
203-869	50:1	120 lb./55 kg	3 (76.2)	180 (12)	2.2 (1.0)	310 (82)
203-868	50:1	400 lb./180 kg	3 (76.2)	180 (12)	2.2 (1.0)	310 (82)
231-028	80:1	Pail Length	3 (76.2)	80 (5.5)	8.8 (3.9)	750 (199)
204-469	80:1	120 lb./55 kg	3 (76.2)	80 (5.5)	8.8 (3.9)	750 (199)
231-029	80:1	400 lb./180 kg	3 (76.2)	80 (5.5)	8.8 (3.9)	750 (199)
<b>PRESIDENT</b>						
965-124*	10:1	Flange Mount	4.25 (108)	180 (12)	85 (39)	20 (5.3)
965-130*	10:1	400 lb./180 kg Cover	4.25 (108)	180 (12)	85 (39)	20 (5.3)
965-129*	10:1	400 lb./180 kg Bung	4.25 (108)	180 (12)	85 (39)	20 (5.3)
205-394	50:1	120 lb./55 kg	4.25 (108)	180 (12)	11 (4.9)	110 (29)
205-395	50:1	400 lb./180 kg	4.25 (108)	180 (12)	11 (4.9)	110 (29)
948-416*	75:1	Pail Length	4.25 (108)	100 (7)	8.25 (3.7)	166 (44)
948-402*	75:1	120 lb./55 kg	4.25 (108)	100 (7)	8.25 (3.7)	166 (44)
948-415*	75:1	400 lb./180 kg	4.25 (108)	100 (7)	8.25 (3.7)	166 (44)
<b>BULLDOG "SINKER"</b>						
205-148	3:1	Bare	7 (178)	120 (8.16)	200 (90)	NA

