

# LUBRICATION EQUIPMENT

K

| Rec. Max. cpm | Air Inlet   | Material Outlet | Stroke Length in. (mm) | Service Kit: Motor | Service Kit: Fluid Section | Data Sheet | Instruction Manual |
|---------------|-------------|-----------------|------------------------|--------------------|----------------------------|------------|--------------------|
| 115           | 3/8 npt(f)  | 1/4 npt(f)      | 3.25 (82.5)            | 236-059            | 236-059                    | 305-577    | 308-262            |
| 115           | 3/8 npt(f)  | 1/4 npt(f)      | 3.25 (82.5)            | 236-059            | 236-059                    | 305-577    | 308-262            |
| 115           | 3/8 npt(f)  | 1/4 npt(f)      | 3.25 (82.5)            | 236-059            | 236-059                    | 305-577    | 308-262            |
| 66            | 3/8 npt(f)  | 1/2 npt(f)      | 3 (76)                 | 206-728            | NA                         | NA         | NA                 |
| 66            | 3/8 npt(f)  | 1/2 npt(f)      | 3 (76)                 | 206-728            | NA                         | NA         | NA                 |
| 66            | 3/8 npt(f)  | 1/2 npt(f)      | 3 (76)                 | 206-728            | NA                         | NA         | NA                 |
| 66            | 3/8 npt(f)  | 1/4 npt(f)      | 3 (76)                 | 206-728            | 204-164                    | NA         | 306-517            |
| 66            | 3/8 npt(f)  | 1/4 npt(f)      | 3 (76)                 | 206-728            | 204-164                    | NA         | 306-517            |
| 66            | 3/8 npt(f)  | 1/4 npt(f)      | 3 (76)                 | 206-728            | 204-164                    | NA         | 306-517            |
| 75            | 3/8 npt(f)  | 1/4 npt(f)      | 3 (76)                 | 206-728            | 236-599                    | NA         | 306-554            |
| 75            | 3/8 npt(f)  | 1/4 npt(f)      | 3 (76)                 | 206-728            | 236-599                    | NA         | 306-554            |
| 75            | 3/8 npt(f)  | 1/4 npt(f)      | 3 (76)                 | 206-728            | 236-599                    | NA         | 306-554            |
| 60            | 1/2 npt(f)  | 3/4 npt(m)      | 4 (102)                | 207-385            | NA                         | NA         | NA                 |
| 60            | 1/2 npt(f)  | 3/4 npt(m)      | 4 (102)                | 207-385            | NA                         | NA         | NA                 |
| 60            | 1/2 npt(f)  | 3/4 npt(m)      | 4 (102)                | 207-385            | NA                         | NA         | NA                 |
| 66            | 3/8 npsm(f) | 3/8 npt(f)      | 4 (102)                | 207-385            | 206-928                    | NA         | 306-674            |
| 66            | 1/2 npsm(f) | 3/8 npt(f)      | 4 (102)                | 207-385            | 206-928                    | NA         | 306-674            |
| 110           | 1/2 npt(f)  | 3/8 npt(f)      | 4 (102)                | 207-385            | 949-707                    | NA         | NA                 |
| 110           | 1/2 npt(f)  | 3/8 npt(f)      | 4 (102)                | 207-385            | 949-707                    | NA         | NA                 |
| 110           | 1/2 npt(f)  | 3/8 npt(f)      | 4 (102)                | 207-385            | 949-707                    | NA         | NA                 |
| 60            | 3/4 npsm(f) | 2 npt(f)        | 4.75 (121)             | 206-734            | NA                         | NA         | 306-642            |

