

LUBRICATION EQUIPMENT

K

Rec. Max. cpm	Air Inlet	Material Outlet	Stroke Length in. (mm)	Service Kit: Motor	Service Kit: Fluid Section	Data Sheet	Instruction Manual
115	3/8 npt(f)	1/4 npt(f)	3.25 (82.5)	236-059	236-059	305-577	308-262
115	3/8 npt(f)	1/4 npt(f)	3.25 (82.5)	236-059	236-059	305-577	308-262
115	3/8 npt(f)	1/4 npt(f)	3.25 (82.5)	236-059	236-059	305-577	308-262
66	3/8 npt(f)	1/2 npt(f)	3 (76)	206-728	NA	NA	NA
66	3/8 npt(f)	1/2 npt(f)	3 (76)	206-728	NA	NA	NA
66	3/8 npt(f)	1/2 npt(f)	3 (76)	206-728	NA	NA	NA
66	3/8 npt(f)	1/4 npt(f)	3 (76)	206-728	204-164	NA	306-517
66	3/8 npt(f)	1/4 npt(f)	3 (76)	206-728	204-164	NA	306-517
66	3/8 npt(f)	1/4 npt(f)	3 (76)	206-728	204-164	NA	306-517
75	3/8 npt(f)	1/4 npt(f)	3 (76)	206-728	236-599	NA	306-554
75	3/8 npt(f)	1/4 npt(f)	3 (76)	206-728	236-599	NA	306-554
75	3/8 npt(f)	1/4 npt(f)	3 (76)	206-728	236-599	NA	306-554
60	1/2 npt(f)	3/4 npt(m)	4 (102)	207-385	NA	NA	NA
60	1/2 npt(f)	3/4 npt(m)	4 (102)	207-385	NA	NA	NA
60	1/2 npt(f)	3/4 npt(m)	4 (102)	207-385	NA	NA	NA
66	3/8 npsm(f)	3/8 npt(f)	4 (102)	207-385	206-928	NA	306-674
66	1/2 npsm(f)	3/8 npt(f)	4 (102)	207-385	206-928	NA	306-674
110	1/2 npt(f)	3/8 npt(f)	4 (102)	207-385	949-707	NA	NA
110	1/2 npt(f)	3/8 npt(f)	4 (102)	207-385	949-707	NA	NA
110	1/2 npt(f)	3/8 npt(f)	4 (102)	207-385	949-707	NA	NA
60	3/4 npsm(f)	2 npt(f)	4.75 (121)	206-734	NA	NA	306-642

